

HD7L-04



WE'RE ALWAYS WATCHING®



Features

- 4K UHD Display (HDMI)
- Support EX-SDI, HD-SDI, TVI, AHD, CVI, 960H, IP
- 2MP, 4MP: 4Channel BNC Input + 2 IP
4K: 2Channel BNC Input + 1 IP
- Support ONVIF
- Support Ethernet POS
- Up to 2HDDs or (1 HDD + 1 eSATA)
- Network Interface - 2x Ethernet 10/100/1G
- Smartphone Viewer Support (Android/iPhone/iPad)



Specifications

HD7L-04	
VIDEO	
Input	4 BNC
Input Resolution	8MP, 4MP, 3MP, 2MP, 960H
Output	1 HDMI, 1VGA, 2BNC (1 HD, 1 SD)
Output Resolution	4K, FHD, SXGA, XGA
RECORDING	
Speed	15fps/ch(4MP), 30fps/ch(2MP)
Resolution	8MP, 4MP, 3MP, 2MP, 960H
AUDIO	
Input	4 RCA
Output	1 HDMI, 1 RCA
INTERFACE	
Sensor In / Out	4 / 1 - NC / NO
USB	2 x USB 2.0
PTZ / Keyboard	2 x RS485 - Terminal Block
ATM / POS	Ethernet POS
NETWORK	
Interface	2 x Ethernet 10/100/1G
Compression	H.264. JPEG
Speed	10fps(4MP), 20fps(2MP)
Resolution	Max. 4MP
STORAGE	
Primary / Enternal	2 HDD or (1 HDD + 1 eSATA)

SYSTEM	
OS	Embedded Linux (Built-in Flash Memory)
Pre / Post-Alarm	5sec /5sec~5min
Recording Mode	Continuous, Event, Schedule
Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time
Backup Interface	USB, Network
Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data
Alarm Action	Buzzer, PIZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push
User	15 Users (Admin, User1 ~ User14)
Network Viewer	Netus, VMS, Web Viewer, Mac Viewer, ACT View HD (iOS, Androld)
ONVIF	ONVIF Profile S
GENERAL	
Dimensions	340 x 60 x 300 mm
Weight(w/o HDD)	3kg
Temp / Humidity	5 ~ 40°C /10% ~80%
Power Supply	12V / 3.3A
Power Consumption	40 Watts